



Patent Application of Hans Ruiz and Glenn Smith

for

**UNIVERSAL ADJUSTABLE EQUIPMENT MOUNT**

**Background-Field of Invention**

This invention relates to equipment mounts used on marine vessels and other water-borne craft. Such equipment mounts are commonly used to mount lights, fishing rods, reels of fishing cable, and other marine equipment.

**Background-Description of Prior Art**

In a water-borne or marine environment, pleasure craft used for recreational purposes have a highly limited amount of space available on their deck areas. When these craft are not large to begin with, the amount of deck space that is available is even more limited. This problem is made even worse when recreational items such as fishing rods, or necessary items, such as lights and boarding ladders, are left on the deck to consume even more of what little space is available. In addition, on typical recreational boats, there is usually not just one fishing rod or one light, but several. This hijacking of space is not the only problem presented by these items left on the deck. They are also dangerous because people could trip over them. Or, during rough seas, they could roll into someone and cause injury. It is therefore imperative in this type of situation that a means is found to mount these items off the deck in a safe, efficient, and inconspicuous manner.

Most of the mounting devices currently available have been developed solely for mounting fishing rods. In addition, most of these are for mounting fishing rods while they, the rods, are in use. Most of them do not have any provision for mounting the rods after they are no longer being used. When they are designed for mounting rods after the rods have been used, they usually exist as single units and therefore put the installer through the hassle of having to mount several one-at-a-time. Most of the others in existence are for only storing the rods after they have been taken off the boat. In addition, they do not address the issue of mounting other items found on the boat, such as lights, dive ladders, and reels of fishing line.

Because of this, a need has arisen for some type of universal mounting device that can not only mount fishing rods but other items as well. It should also be easy to mount and mounted in a place where it does not take up much space. Another necessary feature of this type of mount would be the ability to mount several items on one mount instead of having to install a separate mount for each item that needs to be mounted.

Several mounts have been developed that only partially or barely address these needs. One such mount, or holder, already developed is one used to mount fishing rods in U.S. patent #USO4793086 to Cup, 12/27/88. It is meant for mounting fishing rods and is meant to be attached to the transom, or railing of a boat. However, it is only for a fishing rod and is only meant to mount the fishing rod while it is being used. It holds only two rods, and does not allow for vertical adjustment. Another holder, or mount, is presented in U.S. patent #US4157803 to Mack, 6/12/79. This one has the advantage of housing several rod holders along its body, yet it has drawbacks in that each rod holder cannot be adjusted up or down, or along the length of the body to which it is attached. Ability to adjust the rod holders gives the operator the ability to set

the desired angle of the rod while fishing and the ability to set the rod holders back while the rods are mounted and not being used. In addition, this design only mounts fishing rod holders and no other equipment. Another example pertaining to this class of devices can be found in U.S. patent #US6289627 to Gibbs et al, 9/18/2001. This device, like the one attributed to Mack mentioned previously, has the advantage in that it houses a plurality of rod holders along its main body, which consists of a pair of folding support arms. Like the one attributed to Mack, however, its design does not allow for the individual rod holders to be adjusted. Also like the one attributed to Mack, it only provides for the mounting of fishing rods.

Some important objects of the invention presented here are to provide a versatile, rugged, compact, and adjustable mount that can be used to mount not only fishing rods but also a variety of marine accessories.

### **Objects and Advantages**

The majority of the fishing rod or marine accessory holders, or marine mounting devices in existence are inadequate in that they are either too cumbersome or non-adjustable, or are limited to mounting fishing rods. In addition, in many instances they have to be installed in locations where they are either too conspicuous or they get in the way of crew movement. Some of their designs are bulky, taking up needed space and adding weight to vessels that cannot afford to be weighted down.

On some marine pleasure craft, there may be more than one, if not several, people aboard who have brought their fishing rods along in order to fish with. This large number of rods, along

with other equipment, simply cannot be left on the deck where it could pose a tripping hazard. They need to be brought off the deck to eliminate this potential danger.

As well as being simple in design, the universal adjustable equipment mount presented here provides a compact, strong, durable, adjustable, and convenient way to mount not only fishing rods but other types of marine gear as well.

Accordingly, several objects and advantages of this invention are:

1. This equipment mount is simple in design. It consists of a long, c-shaped cylindrical C-extrusion tube with locking solid round bar end-pieces at both ends. The end-pieces are affixed within the C-extrusion with screws. Along the length of the entire C-extrusion runs an elongated cavity cut into its surface, hence giving it the C-shape when looked at from the side. The C-shaped cavity has horizontal ridges from one end of the C-extrusion to the other end. Inside this cavity along the length of the C-extrusion are inserted several t-shaped slide brackets made of extruded aluminum, getting their name from the fact that they can slide along the length of the C-extrusion on their circular C-shaped base inside this cavity. The slide brackets have a single ridge in the base which holds the desired angle in place by wedging between the ridges in the C-extrusion. The slide brackets are secured by tightening a setscrew through the C-shaped base of each slide bracket. The opposite end of the slide brackets has a t-shaped footpad with screw holes. It is to these slide bracket footpads that fishing rod holders, lights, and other equipment can be attached. There are end-pieces made of short pieces of solid round aluminum bar at each end of the C-extrusion. Attached to and extending outward from each locking end-piece are the mounting brackets at the ends of the C-extrusion. The mounting bracket is a rectangular piece of material with one end bent

perpendicular and at a slight angle, and the other end, with rounded corners which attaches to the end piece. The mounting brackets are secured to the locking end-piece with socket head flat screws. These mounting brackets are used to attach the universal mount to whatever surface the user desires by affixing the mounting bracket to the surface using the three pre-drilled holes in the mounting bracket.

2. The universal mount is compact and does not take up much room. It is comprised of the C-extrusion, the two mounting brackets, the locking end-piece, some screws, and the slide brackets. They are all arranged linearly along the C-extrusion, and the entire assembly is usually attached to the hardtop, or roof, of the boat, where it is out of the way of deck traffic.
3. The universal mount is strong and durable. The C-extrusion and the other components are made of solid, extruded aluminum, and are capable of withstanding many pounds per square inch of pressure and force. The mount is durable because its hard aluminum construction makes it resistant to rust and corrosion.
4. The universal mount is adjustable. Each slide bracket can rotate up or down, and can slide sideways anywhere along the length of the C-extrusion on its base. This is made possible by a single ridge on the slide bracket base which fits between the ridges in the cavity of the C-extrusion and acts as a wedge to guide and secure the desired angle of the slide bracket. A setscrew in the base of the slide bracket expands the base and secures the desired angle.
5. Further adjustment to a desired angle in order to adjust lights or fishing rods may be achieved by tightening a setscrew in the section of the mounting bracket which mates with the end-piece at each end of the C-extrusion.

6. The mounting system is convenient. It is convenient because it is easy to use and easy to mount. Using it involves simply attaching the mounting brackets to the boat, then adjusting the c-extrusion to whatever position is desired and then tightening the socket-head flat screw through the mounting bracket and into the end piece. Mounting the Universal Adjustable Equipment mount to the boat involves a few screws through the mounting brackets. In addition, it does not take up much room, since it is primarily intended to be mounted on the hardtop or roof, of most marine pleasure craft.
7. The Universal Equipment Mount is universal. Although the mounting system comes with a rod holder mounted to each slide-bracket for holding fishing poles, these cylinders can be replaced with other holding devices to hold lights, tools, flags, etc. An entire product accessory repertoire can be introduced to enhance the versatility of the Equipment Mount. The slide bracket is made to easily remove and replace the supplied rod holder with accessories by loosening two screws in the face plate of the slide bracket.

### **Brief Description of Drawings (amended)**

**Drawing amendment explanation.** Review of drawings, as originally submitted, showed incorrect numbering and incorrect descriptions of detail parts. All items were checked to insure unique nomenclature and unique reference characterization. Additionally, the error of using different reference characters (“7” and “8”) to denote the same item in different figures (as pointed out by your review) has been corrected in this amended Reference. The original sheets showing changed notations have been resubmitted for reference along with replacement amended and corrected sheets for submission.

**Figure 1 CANCELLED.** (Remaining figures renumbered)

**Figure 1** is a front-on view of the universal mount, showing two rod holders, two slide bracket face plates, the entire length of the C-extrusion, end pieces inside the C-extrusion, and mounting brackets attached to the end pieces.

**Figure 2** is a cut-away side view showing a side view of the C-extrusion and a view of the slide bracket resting within the cavity of the C-extrusion. The rod holder is mounted to the face of the slide bracket.

**Figure 3** is a side cut-away view of the universal mount depicting the movement of the slide bracket inside the C-extrusion before the tilt angle is adjusted as shown in figure 4.

**Figure 4** is a side cut-away view of the universal mount showing the movement of the slide bracket inside the C-extrusion as the angle of the rod holder is tilted up or down.

**Figure 5** is a front view of the universal mount with an arrow indicating a rod holder which will be demonstrating the sideways movement of the slide bracket as shown in figure 6.

**Figure 6** is a front view showing the movement of the rod holder after the slide bracket is moved along the cavity of the C-extrusion.

**Figure 7** is a close up view of the ridges in the C-extrusion, the single ridge in the base of the slide bracket, the setscrew in the base of the slide bracket and the screw holes in the faceplate of the slide bracket used for mounting the rod holder and other accessories.

**Figure 8** is a close up view of the end-piece within the cavity of the C-extrusion and the screw at the end of the C-extrusion which secures the end piece in place.



**Reference numerals for figures 1-8 (Amended)**

**Figure 1** The original Figure 1 has been cancelled, the remaining Figures have been renumbered and appropriate changes made.

**Figure 1**

1. C-extrusion
2. rod holders
3. mounting bracket, right
4. mounting bracket, left
5. slide brackets
11. locking end-piece
14. socket screw, flat head

**Figure 2**

1. C-extrusion
2. rod holder
4. mounting bracket, left
5. slide bracket
6. screw, button head

**Figure 3**

1. C-extrusion
2. rod holder
3. mounting bracket, right
5. slide bracket

- 6. screw, button head
- 18. Side view of rod holder before movement up or down.

**Figure 4**

- 1. C-extrusion
- 2. rod holder
- 3. mounting bracket, right
- 5. slide bracket
- 6. screw, button head
- 19. Side view of rod holder with an arrow showing the up and down direction of force after movement.

**Figure 5**

- 1. C-extrusion
- 2. rod holders
- 3. mounting bracket, right
- 4. mounting bracket, left
- 11. locking end-piece
- 14. socket screw, flat head
- 20. Front view with an arrow showing the sideways direction of movement or force of the rod holder before movement.

**Figure 6**

- 1. C-extrusion
- 2. rod holders

- 3. mounting bracket, right
- 4. mounting bracket, left
- 11. locking end-piece
- 14. socket screw, flat head
- 21. Front view with an arrow showing the sideways direction of movement or force of the rod holder after movement.

**Figure 7**

- 1. C-extrusion
- 5. slide bracket
- 12. setscrew
- 15. single ridge in the base of the slide bracket
- 16. ridges in the cavity of the C-extrusion
- 17. mounting holes in the faceplate of the slide bracket

**Figure 8**

- 1. C-extrusion
- 11. locking end-piece
- 14. screw, flat head
- 16. ridges in the cavity of the C-extrusion

### **Summary of the Invention**

A Universal Adjustable Equipment Mount for use as a general equipment mount aboard marine craft and comprised of a C-extrusion, slide brackets, mounting brackets, rod holders, locking end-pieces, socket-head flat screws, pan head screws, and setscrews. The rod holders are supplied but are considered optional equipment. They can be detached and replaced with other accessory attachments. Several slide brackets are inserted into and occupy the cavity of the C-extrusion which is cylindrical in shape. The cavity of the C-extrusion has ridges from one end of the C-extrusion to the other end. This gives the equipment mount its horizontal and vertical adjustment versatility. The slide brackets have the ability to slide sideways along the length of the C-extrusion cavity, and can also be tilted up and down on their base. The exact position of the slide brackets is held in place by a ridge on the base of the slide bracket which is wedged between ridges in the cavity of the C-extrusion. The slide bracket positioning is secured by tightening a setscrew through the C-shaped base of each slide bracket. The expansion of the base by the setscrew is part of the operating mechanism permitting multiple adjustment positions. On the opposite end of the slide brackets are holes through a t-shaped faceplate which screws are inserted which enable one to mount a variety of equipment, including lights and fishing rod holders. A pair of supplied mounting brackets mounts the C-extrusion to a selected surface, usually the hardtop of a vessel. The mounting brackets are anchored to the open ends of the C-extrusion by attaching to a pair of locking end-pieces made of solid round bar, which have been inserted into the open ends of the C-extrusion with screws. Socket-head flat screws attach the mounting brackets to the locking end-pieces.

### **Detailed Description and Operation of Invention- Revised Figures 1-8**

Referring in greater detail to the drawings:

Fig. 1 is a front view the universal mount as it would look head-on, as if it were mounted on the hardtop, or roof, of a boat. It shows mounting brackets 3,4 attached to locking end-piece 11 which are attached to the C-extrusion 1 by screw(s) 14. Also shown are rod holders 2 which are mounted on slide brackets 5.

Fig. 2 is a cutaway view from the side showing the slide bracket 5 mounted in the cavity of the C-extrusion 1. The Rod Holder 2 is mounted to the slide bracket 5 and held in place using two socket screws 6. The mounting bracket 4 attaches the universal mount assembly to the boat or auto vehicle.

Fig. 3 is essentially the same view as fig. 2. It is here, however, to give perspective to the up and down movement of the rod holder 2. Pictured here is the rod holder 2 at a location prior to adjustment up as shown in figure 4.

Fig. 4 shows how the slide bracket 5 can be adjusted up or down. The Rod holder 2 is attached to slide bracket 5 and moves in the upward direction of arrow 19 as the height is adjusted. It can also be adjusted downward as well. Recall that slide bracket 5 also moves sideways within the C-extrusion 1 which is anchored to a surface by the mounting bracket 3. The rod holder 2 is attached to slide bracket 5 by two socket head screws 6.

Fig. 5 shows a full complement of four rod holders 2. However, its main purpose is to help explain the sideways movement of the slide brackets hidden underneath the rod holders 2. This arrow 20 illustration is before sideways movement and the next illustration shown in fig. 6 is after sideways movement.

Fig. 6 illustrates by arrow **21** the sideward direction of movement of the rod holder **2** along C-extrusion **1**. The position of the rod holder **2** before movement is shown in figure 5.

Fig. 7 is a close up view of the interaction between the slide bracket **5** and the C-extrusion **1**. The slide bracket **5** occupies the cavity of the C-extrusion **1** where a single ridge **15** on the base of the slide bracket **5** is wedged between the ridges **16** in the C-extrusion **1**. A setscrew **12** expands or contracts the base of the slide bracket **5** to secure the slide bracket **5** within the C-extrusion **1**. Also shown are the holes **17** used for affixing accessories to the faceplate of the slide bracket **5**.

Fig. 8 is a close up of the end-piece **11** affixed in the cavity at one end of the C-extrusion **1** while resting on the ridges **16** along the interior of the C-extrusion **1**. A screw **14** in the C-extrusion **1** secures the end-piece **11** in position.

### **Conclusion, Ramifications, and Scope of Invention.**

After reviewing the above information, the reader will be able to see that the Universal Adjustable Equipment Mount presented here provides a vast improvement over other mounting systems for boats that are currently available. It is simple in design and easy to manufacture. It is compact, and since it mounts to the hardtop, or roof, of a boat, it doesn't take up any room on the deck. In addition to these advantages, other advantages of the Universal Adjustable Equipment Mount are:

It is versatile in that it can mount a variety of equipment besides rod holders. Most mounts currently available only mount rod holders: this mount, however, not only mounts rod holders on the faceplate of the slide bracket, but also other types of equipment such as lights, cable reels, and dive ladders..

It is adjustable. Most of the mounts that exist are not adjustable. This equipment mount is. Its slide brackets, the components to which items such as lights and rod holders are mounted on, can be adjusted up and down; they can also be traversed along the length of the entire equipment mount. This enables the user to great versatility in adjusting lights, fishing rods, or other equipment that has been mounted on the Universal Equipment Mount.

It is unobtrusive. The universal mount does not protrude out far. Also, since it is mounted on the roof of the boat, it is out of the way of most deck activity and does not take up valuable deck space.

While the above description contains many details and specifications, these should not be considered a limitation on the scope of this invention, but rather as a description of one preferred embodiment of this mechanism. Several other variations are possible. Adjustable mounts with

different shapes could be made, or mounts utilizing differently shaped slide brackets or mounting brackets could be made. Other mounts could be made utilizing different materials, such as plastic, aluminum, hardened rubber, or polyurethane. This could be especially helpful if someone were looking for a mount that needed to be extremely light in weight.